



ELECTRICAL INSULATING SHEET 1 X 1.3M

MODEL NO: **ES1000**

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



Refer to instructions



Safe for Live working



Wear protective gloves



Wear protective clothing

1. SAFETY

- WARNING!** Ensure health & safety, local authority and general workshop practice regulations are strictly adhered to when using this product.
- ✓ Familiarise yourself with the product application and limitations, as well as the specific potential hazards peculiar to this product.
- WARNING!** This insulating sheet is intended to be used exclusively for electrical purposes.
- WARNING!** Always use with additional electrical insulation PPE.
- WARNING!** Always use with electrically insulated tools suitable for 1000V safe live working.
- × **DO NOT** bend, fold or compress the insulating sheet.
- × **DO NOT** store or use close to excessive heat.
- × **DO NOT** expose to direct sunlight for long period.
- ✓ Store at an ambient temperature between 10°C and 21°C.
- ✓ Avoid contact with chemical products.

2. INTRODUCTION

Soft insulated sheet suitable for insulating during work in progress where live connectors may be present. Maximum operating voltage 1000V AC. Tested in accordance with IEC 61112. Always use with additional electrical insulation PPE.

3. SPECIFICATION

Model no: ES1000
Maximum operating voltage: 1000V AC
Sheet size: 1.0m x 1.3m

4. OPERATION

- 4.1. Before use, visually inspect the insulating sheet for any defects. If the sheet becomes punctured or damaged it **MUST NOT** be used.
- 4.2. Position insulating sheet to provide maximum protection to user (fig 1).
Insulating sheet can be fixed in place with insulated clamps or insulating PVC sticky tape, not supplied.



5. MAINTENANCE

- 5.1. If the insulating sheet becomes dirty, wash it with soap and water and dry thoroughly.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR



01284 757500



01284 703534



sales@sealey.co.uk



www.sealey.co.uk