

Thank you for purchasing a Sealey Product. Manufactured to a high standard this product will, if used according to these instructions and properly maintained, give you years of trouble free performance.


IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS AND CAUTIONS. USE THIS PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. PLEASE KEEP INSTRUCTIONS SAFE FOR FUTURE USE.

1. SAFETY INSTRUCTIONS

- WARNING!** Ensure all Health and Safety, local authority, and general workshop practice regulations are strictly adhered to when using the puller.
- DO NOT** use puller if damaged or worn.
- Maintain the puller in good and clean condition for best and safest performance.
- Always check that puller is correctly assembled and is square with the workpiece.
- If vehicle is raised, ensure it is adequately supported with axle stands, ramps, etc. as appropriate.
- Wear suitable clothing to avoid snagging. Do not wear jewellery and tie back long hair.
- Wear approved eye protection. A full range of personal safety equipment is available from your Sealey dealer.
- Where possible shield workpiece with canvas or similar to provide protection against failed parts.
- DO NOT** hit workpiece with a hammer if workpiece has not moved with maximum puller force applied. Use a larger capacity puller.
- DO NOT** use the puller for a task it is not designed to perform.
- IMPORTANT!** Always refer to the vehicle manufacturer's service instructions, or proprietary manual, to establish the correct procedure and data. These instructions for use are provided as a guide only.



2. INTRODUCTION AND SPECIFICATIONS



Suitable for wheel arches and other small/lightweight pulls including those around light clusters.

Model No:RE99/09
Length:320mm
Capacity:1.5ton

Model No:RE99/10
Length:160mm
Capacity:1.5ton

3. USING THE WHEEL ARCH PULLER

- 3.1 USING THE PULLERS**
 - 3.1.1 Carefully select the appropriate puller and curvature for the job in hand.
 - 3.1.2 For slight dents and creases the tool can be pulled by hand.
 - 3.1.3 With more severe dents and creases, use of chassis straighteners DZRE84/C or DZRE92/C is recommended. Refer to DZRE84/C or DZRE92/C instructions for detailed information.
- ALWAYS!** Use in conjunction with a safety cable to prevent injury in the event of the puller slipping during pulling operation (See item RE92/SC).

NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. **IMPORTANT:** No liability is accepted for incorrect use of this equipment. **WARRANTY:** Guarantee is 12 months from purchase date, proof of which will be required for any claim. **INFORMATION:** For a copy of our latest catalogue and promotions call us on 01284 757525 and leave your full name and address, including postcode.