

Thank you for purchasing a Sealey product. Manufactured to a high standard this product will, if used according to these instructions and properly maintained, give you years of trouble free performance.

⚠ IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS AND CAUTIONS. USE THIS PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. PLEASE KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.

⚠ WARNING! Before using the tow hitch, read, understand and apply the following:

- **DO NOT** exceed the specified towed and towing vehicle weights.
- **Not for use** on cars or car-derived vans first registered on or after 1st August 1998.
- Using ball hitch
Maximum weight of **towed** vehicle 1500kg.
Maximum weight of **towing** vehicle 3050kg.
- Using pin hitch
Maximum weight of **towed** vehicle 3000kg.
- Never use without the towing pin and the security pin in place.
- Before each use, lightly grease the ball head and check the hitch for damage. If damage is found, rectify before using the hitch.
- The ball hitch is designed for normal road use. If used off-road, where the angular movement between towing and towed vehicles may be great, there is a risk of the female (socket) hitch fouling the neck of the ball and causing damage. Therefore, for off-road use, it is recommended that the trailer is fitted with a ring hitch which can then be coupled to the tow hitch pin.



NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

IMPORTANT: No liability is accepted for incorrect use of this equipment.

WARRANTY: Guarantee is 12 months from purchase date, proof of which will be required for any claim.

INFORMATION: For a copy of our latest catalogue and promotions call us on 01284 757525 and leave your full name and address, including postcode.

