

Circular Split Dies BS 1127(1950), HSS

Whitworth-Pipe Thread G(BSPF), DIN ISO 228

BA-Thread, BS 93

Product Group					I3	Product Group					I3
List-No.					64160	List-No.					64170
Type					adjustable	Type					adjustable
Length of chamfer lead					1,5 Thread	Length of chamfer lead					1,5 Thread
Tolerance					B	Tolerance					normal
Surface					P0	Surface					P0
					Availability						Availability
1/8	28	1	3/8		•	16	133,7	13/16	1/4		•
1/8	28	1 5/16	7/16		•	15	120,9	13/16	1/4		•
1/4	19	1 5/16	7/16		•	14	110,4	13/16	1/4		•
1/8	28	1 1/2	1/2		•	13	101,6	13/16	1/4		•
1/4	19	1 1/2	1/2		•	12	90,9	13/16	1/4		•
3/8	19	1 1/2	1/2		•	10	72,6	13/16	1/4		•
1/4	19	2	5/8		•	9	65,1	13/16	1/4		•
3/8	19	2	5/8		•	8	59,1	13/16	1/4		•
1/2	14	2	5/8		•	7	52,9	13/16	1/4		•
5/8	14	2	5/8		•	6	47,9	13/16	1/4		•
3/4	14	2	5/8		•	5	43,0	13/16	1/4		•
1/2	14	2 1/4	11/16		•	4	38,5	13/16	1/4		•
3/4	14	2 1/4	11/16		•	3	34,8	13/16	1/4		•
7/8	14	2 1/4	11/16		•	2	31,4	13/16	1/4		•
1	11	2 1/4	11/16		•	1	28,2	13/16	1/4		•
3/4	14	3	7/8		•	0	25,4	13/16	1/4		•
7/8	14	3	7/8		•	2	31,4	1	3/8		•
1	11	3	7/8		•	1	28,2	1	3/8		•
1 1/4	11	3	7/8		•	0	25,4	1	3/8		•
1	11	4	1		•						
1 1/4	11	4	1		•						
1 1/2	11	4	1		•						
1 3/4	11	4	1		•						
2	11	4	1		•						

P0-Bright • P1-Steam tempered • P2-Bronze • P3-Moc • P4-Nitrided • P5-TiN • P6-TiCN • P7-HY • P8-TiAlN • P9-TiB